

## WKI-1001 1/2 H.P. SUBMITTAL SHEET

- · Space saving compact design!
- High-speed 2600 r.p.m. permanent magnet motor produces more power per pound.
- · Corrosion resistant grinding components.
- Fast and easy mount system provides a no hassle installation.
- · Removable splash guard is included.
- · Safe for properly sized septic tanks.



DIMENSIONS
Knock-out for dishwasher drain connector sized for 7/8" I.D. / 22mm I.D. rubber hose.
12.11/4" 157/m 157/m 14.12** 1322mm 14.12** 14
Measurements are in inches / mm *Add 5/8" / 16mm or RFI Filter

SPECIFICATIONS		
Motor Horsepower	1/2 H.P.	
Motor Speed R.P.M.	2600	
Voltage	100, 110-130, 220-240, 220-240 CE, 220-240 BEAB	
Hz	50/60	
Amps - Watts	520W (100) 4.5 (110-130), 2.25 (220-240), 475W (220-240 BEAB)	
Motor Type	Permanent Magnet	
Sink Flange	Stainless Steel & Celcon	
Stopper	Positive Seal	
Splash Guard	Removable	
Waste Elbow	ABS	
Feed	Continuous	
Grind Ring	Heavy Gauge Galvanized Steel	
Swivel Impellers	Stainless Steel	
Turntable	Galvanized Steel	
Hopper	Glass Filled Nylon	
Grinding Chamber	Corrosion Proof Glass Filled Polyester	
Bearings	Permanently Lubricated; Sleeve Type	
Overload Protector	Manual Reset Type	
Shipping Weight (lbs.)	8.1	
Pallet Quantity	196	

Due to continued product improvement, system configurations and specifications may change without notice.



## SINKMASTER SA (PTY) LTD Distributors of Food Waste Disposers

TEL: (+27) 0800 111 490/011 476 8787 WWW.SINKMASTER.CO.ZA