

WKI-3300 3/4 H.P. SUBMITTAL SHEET

- High-speed 2700 r.p.m. permanent magnet motor produces more power per pound.
- · Stainless steel grinding components.
- Fast and easy mount system provides a no hassle installation.
- · Removable splash guard is included.
- · Safe for properly sized septic tanks.
- · Sound insulated for quiet operation.



Knock-out for dishwasher drain connector sized for 7/8" LD. / 22mm l.D. rubber hose. 8 ½" 216mm 7 ½" 114½" 386mm 14 ½" 387mm	DIMENSIONS	
216cm 7 ½° 184mm 114 ½° 114 ½° 114 ½° 386mm 5 ½° 38cm	connector sized for 7/8" I.D. / 22mm I.D.	
Measurements are in inches / mm	216cm 7 ½° 184cm 14 ½° 114cm 15 ½° 14 ½° 38cm	

*Add 5/8" / 16mm for RFI Filter

SPECIFICATIONS		
Motor Horsepower	3/4 H.P.	
Motor Speed R.P.M.	2700	
Voltage	100, 110-130, 220-240, 220-240 CE, 220-240 BEAB	
Hz	50/60	
Amps - Watts	720W (100), 6.0 (110-130), 3.0 (220-240), 520W (220-240 BEAB)	
Motor Type	Permanent Magnet	
Power Cord	Attached	
Stopper	Positive Seal	
Sink Flange	Stainless Steel & Celcon	
Splash Guard	Removable	
Waste Elbow	ABS	
Feed	Continuous	
Grind Ring	Stainless Steel	
Swivel Impellers	Cast Stainless Steel	
Turntable	Stainless Steel	
Hopper	Glass Filled Nylon	
Grinding Chamber	Corrosion Proof Glass Filled Polyester	
Bearings	Permanently Lubricated; Sleeve Type	
Overload Protector	Manual Reset Type	
Sound Shell	Yes-Full	
Shipping Weight (lbs.)	13	
Pallet Quantity	100	

Due to continued product improvement, system configurations and specifications may change without notice.



SINKMASTER SA (PTY) LTD

TEL: (+27) 0800 111 490/011 476 8787 WWW.SINKMASTER.CO.ZA